

Do Not Disturb 5B077 color: Patina 77950



PRODUCT SPECIFICATIONS

construction:	Texture Cut/Loop
fiber product:	Solution Q® SD Nylon
protective treatment:	SRS Stain Protection
production yarn weight:	32 oz./sq. yd.
finished pile thickness:	0.152"
gauge:	1/10"
stitches per inch:	12
density:	7,579 oz./yd. ³
weight density:	242,528
pattern repeat:	6" W x 6" L
basic end use:	guest rooms

PERFORMANCE SPECIFICATIONS

flooring radiant panel:	Class 1 (ASTM E-662)
smoke density:	< 450 (ASTM E-662)
static control:	< 3.5KV (AATCC-134)
ada compliance:	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Slumber 5B076 color: Patina 76950



**Texture striations, variation, or slight imperfections are an inherent characteristic of the pattern. Please note Slumber cannot be used in public spaces.*

PRODUCT SPECIFICATIONS

construction:	Texture Cut/Loop
fiber product:	Solution Q® SD Nylon
protective treatment:	SRS Stain Protection
production yarn weight:	32 oz./sq. yd.
finished pile thickness:	0.148"
gauge:	1/10"
stitches per inch:	12
density:	7,784 oz./yd. ³
weight density:	249,088
pattern repeat:	12" W x 12" L
basic end use:	guest rooms

PERFORMANCE SPECIFICATIONS

flooring radiant panel:	Class 1 (ASTM E-662)
smoke density:	< 450 (ASTM E-662)
static control:	< 3.5KV (AATCC-134)
ada compliance:	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Two Step 5B073 color: Quartz 73950



PRODUCT SPECIFICATIONS

construction:	Texture Cut/Loop
fiber product:	Solution Q® SD Nylon
protective treatment:	SRS Stain Protection
production yarn weight:	32 oz./sq. yd.
finished pile thickness:	0.254"
gauge:	1/8"
stitches per inch:	10
density:	4,535 oz./yd. ³
weight density:	145,120
pattern repeat:	1 16/32" W x 3 13/32" L
basic end use:	guest rooms

PERFORMANCE SPECIFICATIONS

flooring radiant panel:	Class 1 (ASTM E-662)
smoke density:	< 450 (ASTM E-662)
static control:	< 3.5KV (AATCC-134)
ada compliance:	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Private Line 5B075 color: Envy 75950



PRODUCT SPECIFICATIONS

construction:	Texture Cut/Loop
fiber product:	Solution Q® SD Nylon
protective treatment:	SRS Stain Protection
production yarn weight:	32 oz./sq. yd.
finished pile thickness:	0.146"
gauge:	1/10"
stitches per inch:	12
density:	7,890 oz./yd. ³
weight density:	252,480
pattern repeat:	2 13/32" W x 12" L
basic end use:	guest rooms

PERFORMANCE SPECIFICATIONS

flooring radiant panel:	Class 1 (ASTM E-662)
smoke density:	< 450 (ASTM E-662)
static control:	< 3.5KV (AATCC-134)
ada compliance:	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Bottom Line 5B074 color: Cocoa 74955



PRODUCT SPECIFICATIONS

construction:	Texture Cut/Loop
fiber product:	Solution Q® SD Nylon
protective treatment:	SRS Stain Protection
production yarn weight:	32 oz./sq. yd.
finished pile thickness:	0.186"
gauge:	$\frac{1}{10}$ "
stitches per inch:	11
density:	6,194 oz./yd. ³
weight density:	198,208
pattern repeat:	$\frac{26}{32}$ " W x $1 \frac{1}{32}$ " L
basic end use:	guest rooms

PERFORMANCE SPECIFICATIONS

flooring radiant panel:	Class 1 (ASTM E-662)
smoke density:	< 450 (ASTM E-662)
static control:	< 3.5KV (AATCC-134)
ada compliance:	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.